

Hose Type	Inches	Dash Size	Crimp Spec
PW - 1 Wire 4000 psi (Black)	3/8"	-6	0.816
PW - 2 Wire 6000 psi (Black)	3/8"	-6	0.817
PW - 1 Wire 4000 psi (Blue)	3/8"	-6	0.816
PW - 2 Wire 6000 psi (Blue)	3/8"	-6	0.817
SAE 100 R1AT / 1SN (1 Wire / Braid)			
	1/4"	-4	0.656
	3/8"	-6	.810
	1/2"	-8	0.955
	5/8"	-10	1.10
	3/4"	-12	1.25
	1"	-16	1.64
	1 1/4"	-20	1.91
	1 1/2"	-24	2.19
	2"	-32	2.736
SAE 100 R2AT / 2SN (2 Wire / Braid)			
	1/4"	-4	0.715
	3/8"	-6	.865
	1/2"	-8	0.999
	5/8"	-10	1.13
	3/4"	-12	1.309
	1"	-16	1.640
	1 1/4"	-20	2.09
	1 1/2"	-24	2.3
	2"	-32	2.91
SAE 100 R16 (2 Wire / Braid)			
	1/4"	-4	0.65
	3/8"	-6	0.819
	1/2"	-8	0.96
	5/8"	-10	1.16
	3/4"	-12	1.282
	1"	-16	1.61
SUPER FLEX 3,000	2"	-32	2.795

Hose Type	Inches	Dash Size	Crimp Spec	
Gator Superflex 3,000	2"	-32	2.86	API fitting
	2"	-32	2.8	Std. fitting
R12				
	1/2"	-8	1.08	
	3/4"	-12	1.39	
	5/8"	-10	1.181	
	1"	-16	1.65	
	1-1/4"	-20	2.055	
	1-1/2"	-24	2.25	

	1-1/2	-24	2.25	
	2"	-32	2.88	Std. fitting
	2"	-32	2.85	API fitting
4SH	3/4"	-12	1.4	
	5/8"	-10	1.19	
	1"	-16	1.65	
	1-1/4"	-20	2.109	
	1-1/2"	-24	2.29	